

Smsn
Hydraulic

HYDRAULIC Q.R.C.

SOCKET MALE	PLUG MALE	SOCKET FEMALE	PLUG FEMALE	SOCKET MALE	PLUG MALE	SOCKET FEMALE	PLUG FEMALE

(AS PER ISO - 7241 A)

(AS PER ISO - 7241 B)

CARBON STEEL ZINC ANODISE

BRASS BODY

CODE	SIZE INCH	W.P Kg/Cm ²	PRICE	CODE	SIZE INCH	W.P Kg/Cm ²	PRICE
HSM - 02	1/4"	350	296.00	KSM - 02	1/4"	75	443.00
HSM - 03	3/8"	350	342.00	KSM - 03	3/8"	75	867.00
HSM - 04	1/2"	350	469.00	KSM - 04	1/2"	45	1249.00
HSM - 05	3/4"	350	697.00	KSM - 05	3/4"	45	1974.00
HSF - 02	1/4"	350	263.00	KSF - 02	1/4"	75	443.00
HSF - 03	3/8"	350	303.00	KSF - 03	3/8"	75	867.00
HSF - 04	1/2"	350	416.00	KSF - 04	1/2"	45	1249.00
HSF - 05	3/4"	350	618.00	KSF - 05	3/4"	45	1974.00
HPM - 02	1/4"	350	128.00	KPM - 02	1/4"	75	190.00
HPM - 03	3/8"	350	145.00	KPM - 03	3/8"	75	372.00
HPM - 04	1/2"	350	201.00	KPM - 04	1/2"	45	535.00
HPM - 05	3/4"	350	299.00	KPM - 05	3/4"	45	846.00
HPF - 02	1/4"	350	113.00	KPF - 02	1/4"	75	190.00
HPF - 03	3/8"	350	129.00	KPF - 03	3/8"	75	372.00
HPF - 04	1/2"	350	178.00	KPF - 04	1/2"	45	535.00
HPF - 05	3/4"	350	265.00	KPF - 05	3/4"	45	846.00

Samson
Hydraulic-Hose

SINGLE STEEL WIRE BRAIDED HYDRAULIC HOSE

Conforms SAE 100 R1 AT / DIN 20022 - ISN / EN 853



1 SN Samson

WRAP FINISH
Temp Range : - 40°C to +100°C
Usage : Hydraulic Oil, Fuel Oil,
Grease Oil, Emulsified Oil.

CODE	I.D.		O.D. (mm)	W.P. (Bar)	B.P. (Bar)	Minin Binding Radius (mm)	Coil Length	PRICE MTR
	(Inch)	(mm)						
SR1 - 06	1/4"	6.4	13.4	225	900	100	100	118.00
SR1 - 08	5/16"	7.9	15.0	215	850	115	100	147.00
SR1 - 10	3/8"	9.5	17.4	180	720	130	100	169.00
SR1 - 13	1/2"	12.7	20.6	160	640	180	50	215.00
SR1 - 16	5/8"	15.9	23.7	130	520	200	50	261.00
SR1 - 19	3/4"	19.0	27.7	105	420	240	50	309.00
SR1 - 25	1"	25.4	35.6	88	350	300	50	407.00
SR1 - 32	1-1/4"	31.8	43.5	63	250	420	50	494.00

Samson
Hydraulic-Hose

DOUBLE STEEL WIRE BRAIDED HYDRAULIC HOSE

Conforms SAE 100 R2 AT / DIN 20022 - 2SN / EN 853



2 SN Samson

WRAP FINISH
Temp Range : - 40°C to +100°C
Usage : Hydraulic Oil, Fuel Oil,
Grease Oil, Emulsified Oil.

CODE	I.D.		O.D. (mm)	W.P. (Bar)	B.P. (Bar)	Minin Binding Radius (mm)	Coil Length	PRICE MTR
	(Inch)	(mm)						
SR2 - 06	1/4"	6.4	15.0	400	1600	100	100	155.00
SR2 - 08	5/16"	7.9	16.6	350	1400	115	100	196.00
SR2 - 10	3/8"	9.5	19.0	330	1320	130	100	215.00
SR2 - 13	1/2"	12.7	22.2	275	1100	180	50	261.00
SR2 - 16	5/8"	15.9	25.4	250	1000	200	50	330.00
SR2 - 19	3/4"	19.0	29.3	215	850	240	50	384.00
SR2 - 25	1"	25.4	38.1	165	650	300	50	537.00
SR2 - 32	1-1/4"	31.8	48.3	125	500	420	50	683.00