



SmsN

(TEMP. GAUGE)
THERMOMETER

DIAL SIZE	63 MM	63 MM	100 MM	100 MM	150 MM	150 MM	63 MM	
CASE / TUBE	304 S.S	304 S.S	304 S.S	304 S.S	304 S.S	304 S.S	IN GALVANIZED STEEL	
STEM	316 S.S	316 S.S	316 S.S	316 S.S	316 S.S	316 S.S	316 S.S	
CONNECTION	1/4" BSP	1/4" BSP	1/2" BSP	1/2" BSP	1/2" BSP	1/2" BSP	1/2" BSP	
TYPE	BOTTOM	BACK	BOTTOM	BACK	BOTTOM	BACK	BACK	
ACCURACY	1.5%	1.5%	1.5%	1.5%	1.5%	1.5%	1.5%	
STEM DIAMETER	D : 6.3 MM		D : 6.3 MM		D : 8 MM		D : 8 MM	
TEMP C°	STEM LEN.	CODE	Rs.	CODE	Rs.	CODE	Rs.	
0°-120°	6"	063T1206	537.00	063B1206	412.00	100T1206	905.00	
0°-120°	12"	063T1212	537.00	063B1212	412.00	100T1212	905.00	
0°-200°	6"	063T2006	537.00	063B2006	412.00	100T2006	905.00	
0°-200°	12"	063T2012	537.00	063B2012	412.00	100T2012	905.00	
0°-300°	6"	063T3006	537.00	063B3006	412.00	100T3006	905.00	
0°-300°	12"	063T3012	537.00	063B3012	412.00	100T3012	905.00	
0°-500°	6"	063T5006	537.00	063B5006	412.00	100T5006	905.00	
0°-500°	12"	063T5012	537.00	063B5012	412.00	100T5012	905.00	
							063W1263	278.00

HOT WATER
THERMOMETER

40/50MM SmsN M.S. / S.S. Pressure Gauge (DIAL DUAL SCALE)

DIAL SIZE	40MM	40MM	50MM	50MM	50MM	50MM	50MM
CASE / TUBE	M.S.	M.S.	M.S.	M.S.	M.S.	M.S.	304S.S./316 S.S
CONN. & MOVE.	BRASS	BRASS	BRASS	BRASS	BRASS	BRASS	ALL S.S. 304
TYPE	DRY	DRY	DRY	DRY	DRY	DRY	DRY
THREAD (BSP)	1/8"	1/8"	1/8"	1/4"	1/8"	1/4"	1/4"
CONNECTION	BACK	BOTTOM	BACK	BACK	BOTTOM	BOTTOM	BOTTOM
ACCURACY	2.5%		2.5%		2.5%		2.5%
(Kg/Cm ²)	PSI	CODE	Rs.	CODE	Rs.	CODE	Rs.
0 - 04	58	40B1004D	106.00	40T1004D	102.00	50B1004D	142.00
0 - 07	100	40B1007D	106.00	40T1007D	102.00	50B1007D	142.00
0 - 10	140	40B1010D	106.00	40T1010D	102.00	50B1010D	142.00
0 - 14	200	40B1014D	106.00	40T1014D	102.00	50B1014D	142.00
0 - 21	300					50B1021D	142.00
						50B1021D	142.00
						50T1021D	137.00
						50T2021D	137.00